

IP NEO C

High-Performing, Ultra-Portable Satellite Terminal

Product Sheet

COBHAM
SATCOM
Connecting the future



Setting new standards

Thuraya IP NEO C is a compact satellite terminal engineered to function on Thuraya's L-band satellite network.

The terminal is designed for the upcoming Thuraya T4-NGS satellite from Space42 offering significantly higher throughput than current L-band constellations. With speeds at 1024 kbps from a single terminal, the IP NEO represents a new era for portable L-band satellite terminals by setting new standards for size, performance and reliability.

The durable magnesium casing and a dust and water resistant design makes it the perfect choice when working off the beaten track, but still dependant on a reliable connection.

Groundbreaking performance

The IP NEO offers the fastest broadband data speeds available for a portable satellite terminal of its size, ensuring reliable connectivity from any location within the Thuraya satellite footprint.

The terminal can operate over the Thuraya T4-NGS satellite, supporting speeds at 1 mbps.

Designed for any environment

The terminal is a compact and rugged satellite antenna designed to provide reliable and secure IP data even in the harshest of environments. Its compact size (225 x 225 x 61.5 mm / 2.1 Kg) and lightweight design make it possible to deliver Internet connectivity straight from a backpack in just seconds.



Broadband satellite connectivity made simple

The terminal is easy to setup and to operate. The user interface is intuitive and can be accessed from a PC or smart device.

The antenna features easy satellite pointing, using audio pointing aid and can be easily deployed in a matter of minutes.

With Thuraya Connect App for Android and IOS you can use your smart device to make calls or easily access the internet even in areas with no terrestrial or cellular coverage.

System features

- Type approved for the Thuraya L-Band network
- Lightweight and rugged IP55 design ensures durability
- Simple to set up and to operate
- Versatile power options with both Power over Ethernet (PoE) and 12 - 24 VDC input
- Supports Space42 eSIM and USIM
- Integrated antenna and transceiver
- Robust connectors with screw threads
- Optional pole mount solution (VESA 50)
- AES-256 Encryption

IP NEO C

High-Speed, Ultra-Portable Satellite Antenna

COBHAM
SATCOM

Specifications

Dimensions (H/W/D):	225 / 225 / 61.5 mm
Weight (incl. battery):	2.1 kg
Data Capabilities:	
> 5° elevation:	Up to 1024 kbps (Rx / Tx)
Voice:	Standard VoIP, Embedded SIP Server
Satellite frequency range:	
Rx	1518.0 - 1559.0 MHz
Tx	1626.5 - 1660.5 MHz 1668.0 - 1675.0 MHz
EIRP:	15.1 dBW
Isotropic gain	13 dBi
GNSS:	GPS, Galileo, Beidou, Glonass
Languages:	ENG, AR, FR, POR, ES, RU, JP, CN
Approvals:	CE, RED, RoHS, WEEE, FCC, UL, RCM Thuraya Type Approval

Power

DC input range:	12 - 24 VDC (max. 10.8 - 33.6 VDC)
PoE input:	PoE (802.3bt Type 3 Class 6 via RJ45)
PoE output:	PoE (802.3at Type 1 Class 2 via RJ45)
Power consumption	
Standby / transmit:	4.5W / 22W (typical)
During charging:	75W (max.)
AC/DC power supply	
Input:	100-240 VAC, 47-63Hz, 64W
Output:	19 VDC
Built-in Battery:	Lithium ion (rechargeable)
Nom. voltage / capacity:	10.8 V / 6.9 Ah
Stand-by time:	Up to 38 hours
Receive:	Up to 5 hours @ 1024 Kbps
Transmit:	Up to 3 hours @ 1024 Kbps
Recharge time:	< 3 hours (0-100%)
Charge temperature:	0°C to 45°C

Environmental conditions

Temperature	
Operational (ambient):	-21°C to +55°C
Storage:	-21°C to +50°C
Water and dust:	IP55 Compliant

Interfaces

WLAN Access Point	802.11 b/g/n/ac
2 x Ethernet Ports:	1 x RJ45 (PoE input for ext. power) 1 x RJ45 (PoE output IP Handset)
User interface:	2 x LED (Status and WLAN), Power Button, Reset Button, Web Interface

Other features

Thuraya Connect App (Available for Android / IOS):
Control your IP NEO with your Smartphone.

Set-up and Router Functionality:

Webserver, NAT Router, Admin control (password protected), DHCP, Network Management, Remote Management, PPPoE

Mobile Gateway:

Ruggedized satellite router with advanced PTT and VoIP capabilities

Package

- IP NEO C Terminal with embedded Lithium-Ion Battery
- AC/DC Power Supply, Euro Power Cord, EU to UK Converter
- Quick Start Guide
- Ethernet Cable

Accessories

- 408050A-009: 12/24V DC cable, 3m open-ended
- 403650B-923: Pole Mount
- 408020A-941: PoE cable with screw connectors, 4m
- 408020A-943: PoE cable with screw connectors, 15m
- 408012A-42000: IP NEO Handset
- 408050A-42000: Mobile Gateway NEO C

THURAYA
SPACE42

For further information please contact:

Cobham Satcom
Lundtoftevej 160
DK-2800 Kgs. Lyngby, Denmark
Tel: +45 3955 8800

